

§ 1918.31

be securely made fast to the vessel, wharf, or dolphins.

Subpart D—Working Surfaces

§ 1918.31 Hatch coverings.

(a) No cargo, dunnage, or other material shall be loaded or unloaded by means requiring the services of employees at any partially opened intermediate deck unless either the hatch at that deck is sufficiently covered or an adequate landing area suitable for the prevailing conditions exists. In no event shall such work be done unless the working area available for such employees extends for a distance of 10 feet (3.05 m) or more fore and aft and athwartships.

(b) Cargo shall not be landed on or handled over a covered hatch or 'tween-decks unless all hatch beams are in place under the hatch covers.

(c) Missing, broken, or poorly fitting hatch covers that would not protect employees shall be reported at once to the officer in charge of the vessel. Pending replacement or repairs by the vessel, work shall not be performed in the section containing the unsafe covers or in adjacent sections unless the flooring is made safe.

(d) Hatch covers and hatch beams not of uniform size shall be placed only in the hatch, deck, and section in which they fit properly.

(e) Small trimming hatches in intermediate decks shall be securely covered or guarded while work is going on in the hatch in which they are found, unless they are actually in use.

§ 1918.32 Stowed cargo and temporary landing surfaces.

(a) Temporary surfaces on which loads are to be landed shall be of sufficient size and strength to permit employees to work safely.

(b) When the edge of a hatch section or of stowed cargo may constitute a fall hazard to an employee, the edge shall be guarded by a vertical safety net, or other means providing equal protection, to prevent an employee from falling. When the employer can demonstrate that vertical nets or other equally effective means of guarding cannot be used due to the type of cargo, cargo stowage, or other cir-

29 CFR Ch. XVII (7–1–11 Edition)

cumstances, a trapeze net shall be rigged at the top edge of the elevation or other means shall be taken to prevent injury if an employee falls. Safety nets shall be maintained in good condition and be of adequate strength for the purpose intended.

(c) When two gangs are working in the same hatch on different levels, a vertical safety net shall be rigged and securely fastened to prevent employees or cargo from falling. Safety nets shall be maintained in good condition and be of adequate strength for the purpose intended.

§ 1918.33 Deck loads.

(a) Employees shall not be permitted to pass over or around deck loads unless there is a safe route of passage.

(b) Employees giving signals to crane operators shall not be permitted to walk over deck loads from rail to coaming unless there is a safe route of passage. If it is necessary to stand or walk at the outboard or inboard edge of the deck load having less than 24 inches (.61 m) of bulwark, rail, coaming, or other protection, those employees shall be provided with protection against falling from the deck load.

§ 1918.34 Other decks.

(a) Cargo shall not be worked on decks that were not designed to support the load being worked.

(b) Grated decks shall be properly placed, supported, maintained and designed to support employees.

§ 1918.35 Open hatches.

Open weather deck hatches around which employees must work that are not protected to a height of 24 inches (.61 m) by coamings shall be guarded by taut lines or barricades at a height of 36 to 42 inches (.91 to 1.07 m) above the deck, except on the side on which cargo is being worked. Any portable stanchions or uprights used shall be supported or secured to prevent accidental dislodgement.

§ 1918.36 Weather deck rails.

Removable weather deck rails shall be kept in place except when cargo operations require them to be removed, in which case they shall be replaced as

soon as such cargo operations are completed.

§ 1918.37 Barges.

(a) Walking shall be prohibited along the sides of covered lighters or barges with coamings or cargo more than five feet (1.52 m) high unless a three-foot (.91 m) clear walkway or a grab rail or taut handline is provided.

(b) Walking or working shall be prohibited on the decks of barges to be loaded unless the walking or working surfaces have been determined by visual inspection to be structurally sound and maintained properly. If, while discharging a barge, an unsound deck surface is discovered, work shall be discontinued and shall not be resumed until means have been taken to ensure a safe work surface.

[62 FR 40202, July 25, 1997, as amended at 65 FR 40944, June 30, 2000]

Subpart E—Opening and Closing Hatches

§ 1918.41 Coaming clearances.

(a) *Weather decks.* If a deck load (such as lumber or other smooth sided deck cargo) more than five feet (1.52 m) high is stowed within three feet (.91 m) of the hatch coaming and employees handling hatch beams and hatch covers are not protected by a coaming at least 24-inch (.61 m) high, a taut handline shall be provided along the side of the deckload. The requirements of § 1918.35 are not intended to apply in this situation.

(b) *Intermediate decks.* (1) There shall be a three-foot (.91 m) working space between the stowed cargo and the coaming at both sides and at one end of the hatches with athwartship hatch beams, and at both ends of those hatches with fore and aft hatch beams, before intermediate deck hatch covers and hatch beams are removed or replaced. Exception: The three-foot (.91 m) clearance is not required on the covered portion of a partially open hatch, nor is it required when lower decks have been filled to hatch beam height with cargo of such a nature as to provide a safe surface upon which employees may work.

(2) For purposes of paragraph (b)(1) of this section, fitted gratings that are in good condition shall be considered a part of the decking when properly placed within the three-foot (.91 m) area.

(c) Grab rails or taut handlines shall be provided for the protection of employees handling hatch beams and hatch covers, when bulkheads, lockers, reefer compartments or large spare parts are within three feet (.91 m) of the coaming.

(d) The clearances in this section do not apply to hatches opened or closed solely by hydraulic or other mechanical means; except that, in all cases in which the three-foot (.91 m) clearance does not exist, cargo that is stowed within three feet (.91 m) of the edge of the hatch shall be adequately secured to prevent cargo from falling into the hold.

[62 FR 40202, July 25, 1997, as amended at 65 FR 40944, June 30, 2000]

§ 1918.42 Hatch beam and pontoon bridles.

(a) Hatch beam and pontoon bridles shall be:

(1) Long enough to reach the holes, rings, or other lifting attachments on the hatch beams and pontoons easily;

(2) Of adequate strength to lift the load safely; and

(3) Properly maintained, including covering or blunting of protruding ends in wire rope splices.

(b) Bridles for lifting hatch beams shall be equipped with toggles, shackles, or hooks, or other devices of such design that they cannot become accidentally dislodged from the hatch beams with which they are used. Hooks other than those described in this section may be used only when they are hooked into the standing part of the bridle. Toggles, when used, shall be at least one inch (2.54 cm) longer than twice the largest diameter of the holes into which they are placed.

(c) Bridles used for lifting pontoons and plugs shall have the number of legs required by the design of the pontoon or plug, and all of which shall be used. Where any use of a bridle requires fewer than the number of legs provided, idle legs shall be hung on the hook or